



## ENMED® ENM - 102 Disposable Protective Coverall TYPE 5-B/6-B

The ENMED ENM - 102 Protective Coverall is designed to help protect against: hazardous dusts (Type 5) and light liquid splashes (Type 6).

### Key Features

- Helps provide basic protection against dusts and light liquid splashes
- Elasticated waist, ankles, and wrists for convenience and freedom of movement
- Two-way zipper with storm flap (including tape tabs) for convenience and additional protection

### Comfort and Protection



Liquid Protection

Type 6 - Light Liquid Splashes  
(EN 13034:2005 + A1:2009)



Dust Protection

Type 5 - Solid Airborne Particulates  
EN ISO 13982-1:2004



Anti-static

Anti-static coating\* on both sides  
(EN 1149-5:2008)



Biohazard

TYPE 5-B & 6-B – Infective Agents  
(EN14126:2003)

### Materials

Suit	Multilayer SMS Fabric Laminated
Zipper	Metal / Nylon / Polyester Braid
Elastic	Neoprene Rubber (Latex Free)
Thread	Polyester

This product does not contain components made from natural rubber latex.










### Approvals

CE approved under PPE Directive (EU) 2016/425, Category III  
Certification: Universal Sertifikasyon ve Gözetim Hiz. Tic. Ltd. Şti.  
Notified Body Number: 2163

### Storage and Disposal

- Store in dry, clean conditions in original packaging, away from direct sunlight, sources of high temperature, and solvent vapours
- Store within the temperature range -5°C to +25°C and with relative humidity below 80%
- Expected shelf life is three years from date of manufacture when stored as stated
- Replace garments if damaged, heavily contaminated or in accordance with local work practice or regulations
- Handle and dispose of contaminated garments with care and in accordance with applicable regulations

### Limited Use

	DO NOT RE USE		DO NOT BLEACH		DO NOT IRON
	DO NOT DRY CLEAN		FLAMMABLE KEEP AWAY FROM SPARKS OF FLAMES		CONSULT INSTRUCTIONS FOR USE
	DO NOT WASH LAUNDERING IMPACTS UPON PROTECTIVE PERFORMANCE		DO NOT MACHINE DRY		CAUTION

### Warnings and Limitations

Before use read and understand all user instructions and be sure that the product is suitable for the application and fitted correctly. Product must never be altered or modified. Prior to use inspect the clothing for any damage that could affect its protective function. Replace any damaged clothing. Care should be taken when removing contaminated garments, so as not to contaminate the user with any hazardous substances. If garments are contaminated, then decontamination procedures should be followed prior to removal of the garment. The wearing of chemical protective clothing may cause head stress if appropriate consideration is not given to the workplace environment. Appropriate under garments should be considered to minimize head stress or damage your garment.

### Do not use for:

Contact with heavy oils, sparks or flame, or combustible liquids; Environments with high mechanical risks (abrasions, tears, cuts); Contact with hazardous substances beyond Type 5/6 certification; Environments with conditions of excessive heat.

## Applications and Performance


<b>Non-Hazardous Particulates</b>	Yes	<b>Hazardous Dusts &amp; Fibres</b>	Yes
<b>Non-Hazardous Liquid Splash</b>	Yes	<b>Hazardous Liquid Splash</b>	Yes, if chemical is compatible with suit material†
<b>Non-Hazardous Liquid Spray</b>	Yes	<b>Hazardous Liquid Spray</b>	Yes, if chemical is compatible with suit material†
<b>Liquid Continuous Contact/ Immersion</b>	No	<b>Acids/Alkalis</b>	Yes, if chemical is compatible with suit material†
<b>Gases and Vapours</b>	No	<b>Organic Solvents</b>	Yes, if chemical is compatible with suit material†

Typical applications may include asbestos inspection, coal dust in power plants, metal polishing, light-duty building cleaning, machine or vehicle maintenance, paint spraying, pharmaceutical, general industrial clean-up, insulation laying, woodworking, general powder handling, food processing, blood, bodily fluids and environmentally controlled clean room applications.

## Sizing

An appropriate size garment should be selected to allow sufficient movement for the task.

SIZE	HEIGHT	CHEST
S	189 cm	56 cm
M	194 cm	60 cm
L	199 cm	64 cm
XL	204 cm	68 cm
2XL	212 cm	72 cm
3XL	221 cm	76 cm



\*\*Compatible with ANSI/ISEA 101-2014

### Important Notice

This guide is only an outline. It should not be used as the only means for selecting protective clothing. Before using any protective clothing, the wearer must read and understand the user instructions for each product. Specific country legislation must be observed. If in doubt, contact a safety professional. Selection of the most appropriate PPE will depend on the particular situation and should only be made by a competent person knowledgeable of the actual working conditions and the limitations of PPE.

Final determination as to the suitability of these products for a particular situation is the employer's responsibility. This information is subject to revision at any time. Always read and follow all User Instructions supplied with your ENMED Protective Coveralls in order to ensure correct operation. If you have questions contact ENMED Technical Service.

LIMITATION OF LIABILITY: Except as provided above, ENMED shall not be liable or responsible for any loss or damage, whether direct, indirect, incidental, special or consequential arising out of the sale, use or misuse of ENMED products, or the user's inability to use such products.

### Central Address

Atatürk Mah. 31043 Sk. Kubat Apt.  
No: 8/B Mezitli / MERSİN/TURKEY

### Organized Industrial Zone Address

Çilek Mah. 63150 Sk. No:3 Akdeniz / MERSİN

### Free Zone Mask Factory

Karaduvar Mah. Serbest Bölge 7. Cad. No: 21 33020 Mersin/TURKEY

### Free Zone Textile Factory

Karaduvar mahallesi serbest bölge 18. cadde  
dış kapı no:9 iç kapı no Z1 Akdeniz/MERSİN